

Safety Data Sheet

DRYDEN

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **DTR-LINE DRYDEN COLOURTONES**

Synonyms

Dryden Woodoil 10 Colourtone TR Autumn 500mL
Dryden Woodoil 10 Colourtone TR Custom 500mL
Dryden Woodoil 10 Colourtone TR Soft Gry 500mL
Dryden Woodoil 10 Colourtone TR Dark Oak 500mL
Dryden Woodoil 10 Colourtone TR Karaka 500mL
Dryden Woodoil 10 Colourtone TR Beech 500mL
Dryden Woodoil 10 Colourtone TR Birch 500mL
Dryden Woodoil 10 Colourtone TR Barque 500mL
Dryden Woodoil 10 Colourtone TR Teak 500mL
Dryden Woodoil 10 Colourtone TR Black-X 500mL
Dryden Woodoil 10 Colourtone TR Cedar 500mL
Dryden Woodoil 10 Colourtone TR Charcoal 500mL
Dryden Woodoil 10 Colourtone TR Cumulus 500mL
Dryden Woodoil 10 Colourtone TR Copper 500mL
Dryden Woodoil 10 Colourtone TR Cypress 500mL
Dryden Woodoil 10 Colourtone TR Dryhills 500mL
Dryden Woodoil 10 Colourtone TR Dark 500mL
Dryden Woodoil 10 Colourtone TR Dune 500mL
Dryden Woodoil 10 Colourtone TR Dusk 500mL
Dryden Woodoil 10 Colourtone TR Drifwood 500mL
Dryden Woodoil 10 Colourtone TR Elm 500mL
Dryden Woodoil 10 Colourtone TR Goldleaf 500mL
Dryden Woodoil 10 Colourtone TR Ironsand 500mL
Dryden Woodoil 10 Colourtone TR Larch 500mL
Dryden Woodoil 10 Colourtone TR Midnight 500mL
Dryden Woodoil 10 Colourtone TR Lite Oak 500mL
Dryden Woodoil 10 Colourtone TR Oropo 500mL
Dryden Woodoil 10 Colourtone TR Platinum 500mL
Dryden Woodoil 10 Colourtone TR Redwood 500mL
Dryden Woodoil 10 Colourtone TR Silver Grey 500mL
Dryden Woodoil 10 Colourtone TR Slate 500mL
Dryden Woodoil 10 Colourtone TR Storm 500mL
Dryden Woodoil 10 Colourtone TR Stone 500mL
Dryden Woodoil 10 Colourtone TR Walnut 500mL
Dryden Woodoil 10 Colourtone TR Wcedar 500mL
Dryden Woodoil 10 Colourtone TR Sherwood 500mL
Dryden Woodoil 10 Colourtone TR Manhatan 500mL
Dryden Woodoil 10 Colourtone TR Woodybay 500mL
Dryden Woodoil 10 Colourtone TR Lignum 500mL
Dryden Woodoil 10 Colourtone TR Blonde 500mL
Dryden Woodoil 10 Colourtone TR Blk Teak 500mL
Dryden Woodoil 4 Colourtone TR Autumn 200mL
Dryden Woodoil 4 Colourtone TR Custom 200mL
Dryden Woodoil 4 Colourtone TR Soft Grey 200mL
Dryden Woodoil 4 Colourtone TR Dark Oak 200mL
Dryden Woodoil 4 Colourtone TR Karaka 200mL
Dryden Woodoil 4 Colourtone TR Beech 200mL
Dryden Woodoil 4 Colourtone TR Birch 200mL
Dryden Woodoil 4 Colourtone TR Barque 200mL
Dryden Woodoil 4 Colourtone TR Teak 200mL
Dryden Woodoil 4 Colourtone TR Black-X 200mL
Dryden Woodoil 4 Colourtone TR Cedar 200mL
Dryden Woodoil 4 Colourtone TR Charcoal 200mL

Product Code

DTRW0373-500ML
DTRW0374-500ML
DTRW0375-500ML
DTRW0376-500ML
DTRW0377-500ML
DTRW0378-500ML
DTRW0379-500ML
DTRW0380-500ML
DTRW0381-500ML
DTRW0382-500ML
DTRW0383-500ML
DTRW0456-500ML
DTRW0384-500ML
DTRW0385-500ML
DTRW0386-500ML
DTRW0387-500ML
DTRW0388-500ML
DTRW0389-500ML
DTRW0390-500ML
DTRW0391-500ML
DTRW0392-500ML
DTRW0393-500ML
DTRW0394-500ML
DTRW0395-500ML
DTRW0396-500ML
DTRW0397-500ML
DTRW0398-500ML
DTRW0399-500ML
DTRW0400-500ML
DTRW0401-500ML
DTRW0402-500ML
DTRW0403-500ML
DTRW0404-500ML
DTRW0405-500ML
DTRW0406-500ML
DTRW0407-500ML
DTRW0408-500ML
DTRW0409-500ML
DTRW0410-500ML
DTRW0411-500ML
DTRW0450-500ML
DTRW0373-200ML
DTRW0374-200ML
DTRW0375-200ML
DTRW0376-200ML
DTRW0377-200ML
DTRW0378-200ML
DTRW0379-200ML
DTRW0380-200ML
DTRW0381-200ML
DTRW0382-200ML
DTRW0383-200ML
DTRW0456-200ML

Bar Code

9400513211923
9400513211930
9400513211947
9400513211954
9400513211961
9400513211978
9400513211985
9400513211992
9400513212203
9400513212210
9400513212227
9400513212234
9400513212241
9400513212258
9400513212265
9400513212272
9400513212289
9400513212296
9400513212302
9400513212319
9400513212326
9400513212333
9400513212340
9400513212357
9400513212364
9400513212371
9400513212388
9400513212395
9400513212401
9400513212418
9400513212425
9400513212432
9400513212449
9400513212456
9400513212463
9400513212470
9400513212517
9400513212524
9400513212531
9400513212548
9400513212555
9400513212562
9400513212579
9400513212586
9400513212593
9400513212609
9400513212616
9400513212623
9400513212630
9400513212647
9400513212654
9400513212661
9400513212678

Safety Data Sheet

DRYDEN

Dryden Woodoil 4 Colourtone TR Cumulus 200mL	DTRW0384-200ML	9400513212685
Dryden Woodoil 4 Colourtone TR Copper 200mL	DTRW0385-200ML	9400513212692
Dryden Woodoil 4 Colourtone TR Cypress 200mL	DTRW0386-200ML	9400513212708
Dryden Woodoil 4 Colourtone TR Dryhills 200mL	DTRW0387-200ML	9400513212715
Dryden Woodoil 4 Colourtone TR Dark 200mL	DTRW0388-200ML	9400513212722
Dryden Woodoil 4 Colourtone TR Dune 200mL	DTRW0389-200ML	9400513212739
Dryden Woodoil 4 Colourtone TR Dusk 200mL	DTRW0390-200ML	9400513212746
Dryden Woodoil 4 Colourtone TR Driftwood 200mL	DTRW0391-200ML	9400513212753
Dryden Woodoil 4 Colourtone TR Elm 200mL	DTRW0392-200ML	9400513212760
Dryden Woodoil 4 Colourtone TR Gold Leaf 200mL	DTRW0393-200ML	9400513212777
Dryden Woodoil 4 Colourtone TR Ironsand 200mL	DTRW0394-200ML	9400513212784
Dryden Woodoil 4 Colourtone TR Larch 200mL	DTRW0395-200ML	9400513212791
Dryden Woodoil 4 Colourtone TR Midnight 200mL	DTRW0396-200ML	9400513212807
Dryden Woodoil 4 Colourtone TR Lite Oak 200mL	DTRW0397-200ML	9400513212814
Dryden Woodoil 4 Colourtone TR Oropo 200mL	DTRW0398-200ML	9400513212821
Dryden Woodoil 4 Colourtone TR Platinum 200mL	DTRW0399-200ML	9400513212838
Dryden Woodoil 4 Colourtone TR Redwood 200mL	DTRW0400-200ML	9400513212845
Dryden Woodoil 4 Colourtone TR Silvgrey 200mL	DTRW0401-200ML	9400513212852
Dryden Woodoil 4 Colourtone TR Slate 200mL	DTRW0402-200ML	9400513212869
Dryden Woodoil 4 Colourtone TR Storm 200mL	DTRW0403-200ML	9400513212876
Dryden Woodoil 4 Colourtone TR Stone 200mL	DTRW0404-200ML	9400513212883
Dryden Woodoil 4 Colourtone TR Walnut 200mL	DTRW0405-200ML	9400513212890
Dryden Woodoil 4 Colourtone TR Weathered Cedar 200mL	DTRW0406-200ML	9400513212906
Dryden Woodoil 4 Colourtone TR Sherwood 200mL	DTRW0407-200ML	9400513212913
Dryden Woodoil 4 Colourtone TR Manhattan 200mL	DTRW0408-200ML	9400513212920
Dryden Woodoil 4 Colourtone TR Woodybay 200mL	DTRW0409-200ML	9400513212937
Dryden Woodoil 4 Colourtone TR Lignum 200mL	DTRW0410-200ML	9400513212944
Dryden Woodoil 4 Colourtone TR Blonde 200mL	DTRW0411-200ML	9400513212951
Dryden Woodoil 4 Colourtone TR Black Teak 200mL	DTRW0450-200ML	9400513212968
Dryden Woodoil 1 Colourtone TR Autumn 50mL	DTRW0373-50ML	9400513212975
Dryden Woodoil 1 Colourtone TR Custom 50mL	DTRW0374-50ML	9400513212982
Dryden Woodoil 1 Colourtone TR Soft Grey 50mL	DTRW0375-50ML	9400513212999
Dryden Woodoil 1 Colourtone TR Dark Oak 50mL	DTRW0376-50ML	9400513213002
Dryden Woodoil 1 Colourtone TR Karaka 50mL	DTRW0377-50ML	9400513213019
Dryden Woodoil 1 Colourtone TR Beech 50mL	DTRW0378-50ML	9400513213026
Dryden Woodoil 1 Colourtone TR Birch 50mL	DTRW0379-50ML	9400513213033
Dryden Woodoil 1 Colourtone TR Barque 50mL	DTRW0380-50ML	9400513213040
Dryden Woodoil 1 Colourtone TR Teak 50mL	DTRW0381-50ML	9400513213057
Dryden Woodoil 1 Colourtone TR Black-X 50mL	DTRW0382-50ML	9400513213064
Dryden Woodoil 1 Colourtone TR Cedar 50mL	DTRW0383-50ML	9400513213071
Dryden Woodoil 1 Colourtone TR Charcoal 50mL	DTRW0456-50ML	9400513213088
Dryden Woodoil 1 Colourtone TR Cumulus 50mL	DTRW0384-50ML	9400513213095
Dryden Woodoil 1 Colourtone TR Copper 50mL	DTRW0385-50ML	9400513213101
Dryden Woodoil 1 Colourtone TR Cypress 50mL	DTRW0386-50ML	9400513213118
Dryden Woodoil 1 Colourtone TR Dryhills 50mL	DTRW0387-50ML	9400513213125
Dryden Woodoil 1 Colourtone TR Dark 50mL	DTRW0388-50ML	9400513213132
Dryden Woodoil 1 Colourtone TR Dune 50mL	DTRW0389-50ML	9400513213149
Dryden Woodoil 1 Colourtone TR Dusk 50mL	DTRW0390-50ML	9400513213156
Dryden Woodoil 1 Colourtone TR Drifwood 50mL	DTRW0391-50ML	9400513213163
Dryden Woodoil 1 Colourtone TR Elm 50mL	DTRW0392-50ML	9400513213170
Dryden Woodoil 1 Colourtone TR Gold Leaf 50mL	DTRW0393-50ML	9400513213187
Dryden Woodoil 1 Colourtone TR Ironsand 50mL	DTRW0394-50ML	9400513213194
Dryden Woodoil 1 Colourtone TR Larch 50mL	DTRW0395-50ML	9400513213200
Dryden Woodoil 1 Colourtone TR Midnight 50mL	DTRW0396-50ML	9400513213217
Dryden Woodoil 1 Colourtone TR Lite Oak 50mL	DTRW0397-50ML	9400513213224
Dryden Woodoil 1 Colourtone TR Oropo 50mL	DTRW0398-50ML	9400513213231
Dryden Woodoil 1 Colourtone TR Platinum 50mL	DTRW0399-50ML	9400513213248
Dryden Woodoil 1 Colourtone TR Redwood 50mL	DTRW0400-50ML	9400513213255
Dryden Woodoil 1 Colourtone TR Silvgrey 50mL	DTRW0401-50ML	9400513213262
Dryden Woodoil 1 Colourtone TR Slate 50mL	DTRW0402-50ML	9400513213279
Dryden Woodoil 1 Colourtone TR Storm 50mL	DTRW0403-50ML	9400513213286
Dryden Woodoil 1 Colourtone TR Stone 50mL	DTRW0404-50ML	9400513213293

Safety Data Sheet

DRYDEN

Dryden Woodoil 1 Colourtone TR Walnut 50mL	DTRW0405-50ML	9400513213309
Dryden Woodoil 1 Colourtone TR Weathered Cedar 50mL	DTRW0406-50ML	9400513213316
Dryden Woodoil 1 Colourtone TR Sherwood 50mL	DTRW0407-50ML	9400513213323
Dryden Woodoil 1 Colourtone TR Manhattan 50mL	DTRW0408-50ML	9400513213330
Dryden Woodoil 1 Colourtone TR Woodybay 50mL	DTRW0409-50ML	9400513213347
Dryden Woodoil 1 Colourtone TR Lignum 50mL	DTRW0410-50ML	9400513213354
Dryden Woodoil 1 Colourtone TR Blonde 50mL	DTRW0411-50ML	9400513213361
Dryden Woodoil 1 Colourtone TR Black Teak 50mL	DTRW0450-50ML	9400513213378

Recommended use: Tinter

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd
Company No.: 55 133 404 118 / Co. 2355191
Street Address: 150 Hutt Park Road
Lower Hutt
New Zealand
Telephone: 0800 800 424

Emergency Telephone number: Australia – 1800 220 770; New Zealand – 0800 220 770

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard: HSR002669 - Surface Coatings and Colourants (Flammable, Carcinogenic) Group Standard 2020



Signal Word
Danger

Hazard Classifications

Flammable Liquids - Category 3
Aspiration Hazard - Category 1
Skin Corrosion/Irritation - Category 2
Sensitisation - Skin - Category 1
Carcinogenicity - Category 2
Toxic to Reproduction - Category 2
Specific Target Organ Toxicity following Single Exposure - Category 3 - Narcotic Effects
Specific Target Organ Toxicity following Repeated Exposure - Category 2

Hazard Statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer .
H361 Suspected of damaging fertility or the unborn child .
H373 May cause damage to organs through prolonged or repeated exposure.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Safety Data Sheet

DRYDEN

P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust, fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P281	Use personal protective equipment as required.

Response Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.

Storage Precautionary Statements

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal Precautionary Statement

P501	Dispose of contents/container in accordance with local, regional, national and international regulations.
------	---

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Distillates, petroleum, hydrotreated light	64742-47-8	<75 % (w/w)
Naphtha, petroleum, hydrotreated heavy	64742-48-9	<30 % (w/w)
Xylene	1330-20-7	<10 % (w/w)
Methyl ethyl ketoxime	96-29-7	<1 % (w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Y

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Xylene	50	217			

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Safety Data Sheet

DRYDEN

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Various
Odour:	Solvent
Solubility:	Insoluble in water.
Specific Gravity:	N Av
Relative Vapour Density (air=1):	>1
Vapour Pressure:	N Av
Flash Point (°C):	>23
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
pH:	N App
Viscosity:	<20.5 mm ² /s @ 40 °C
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Safety Data Sheet

DRYDEN

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0$ mg/L for vapours or $LC_{50} > 5.0$ mg/L for dust and mist.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as Aspiration Hazard - Category 1

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as a Category 2 - Substances that are suspected human carcinogens.

Reproductive toxicity (including via lactation): This material has been classified as a Category 2 - Substances that are suspected human reproductive or developmental toxicants.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 2 - Substances that are harmful to human target organs or systems.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Chronic aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): > 100 mg/L, where the substance is not rapidly degradable and/or $BCF < 500$ and/or $\log Kow < 4$.

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Safety Data Sheet

DRYDEN

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14
Limited Quantities 5 L

Proper Shipping Name: PAINT RELATED MATERIAL

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

Safety Data Sheet

DRYDEN

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: PAINT RELATED MATERIAL

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

NZ EPA Status: All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

EPA Group Standard: HSR002669 - Surface Coatings and Colourants (Flammable, Carcinogenic) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: First Issue

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.