

DRYDEN[®]

THE NATURAL CHOICE FOR YOUR TIMBER

LiquidTimber Clean – Product Data Sheet

1. PRODUCT ATTRIBUTES

This product:

- can be used to freshen and brighten dulled timber and help improve cosmetic appearance.
- can be used to improve cosmetic stains and blemishes from metal or aluminium filings (iron stains), caustic splash from concreting, aggregate drive wash, cement-based tile adhesives, dust from cutting concrete, fibrolite, masonry blocks and accumulated environmental grime, exhaust smut and severe watermarks.
- applies easily and rapidly.

Because of the spotty appearance, cosmetic stains may be mistaken for mould. For general cleaning of mould, oxidised (silvering) timber, dirt, grime, and mild watermarks, we recommend using *Dryden SurfaceCleaner* in accordance with the product data sheet for that product.

2. PRODUCT SUITABILITY

This product can be applied to most timbers including new, restored, dressed, bandsawn, oiled and some stained or previously coated polyurethane timbers.

If timber is coated with *Dryden WoodOil* with a *Dryden Colourtone+* added, recoating will be required, as this product will remove the colour (although the *Dryden WoodOil* will remain in the timber).

Before applying fully, test this product on an inconspicuous area to ensure suitability.

3. COVERAGE RATES

Approximate coverage rates for this product are as follows:

Product mixture	Coverage rate (m ² /litre)
Diluted product (50% of product mixed with 50% clean water)	16
Undiluted product (neat)	8

However, coverage rates may vary due to severity of the cosmetic stain or blemish, timber porosity and environmental conditions when applying.

4. APPLICATION TOOLS

- Small mist sprayer
- Bucket and sponge

5. PRODUCT STORAGE

We recommend that this product is stored together with like product, off the ground, in a dry and well-ventilated area and at a consistent and moderated temperature.

6. APPLICATION ENVIRONMENT

The timber must be dry. There must be dry conditions with no expected rain for 6 to 8 hours.

Apply either in shade or on an overcast day to prevent the product drying during the application process, as direct sun and warmth will evaporate the product and it will not remain active on the surface.

7. SURFACE AND SURROUNDING AREA PREPARATION

Sweep or brush away any loose debris from the surface.

If applying above the roof line, disconnect down pipes before applying and rinse gutters and roof area after applying and before reconnecting down pipes.

Cover and protect any painted surfaces, such as joinery and hardware, and surrounding areas, such as gardens and ponds, that may be splashed or get wet during application, as this product will mark any painted surfaces or surrounding areas that are not protected. If this product comes into contact with any painted surfaces or surrounding areas, rinse off immediately.

8. PERSONAL PROTECTION

When applying this product, we recommend you wear personal protective equipment, such as gloves, eye protection and face protection. After applying this product, we recommend you wash skin using detergent and hot water.

For further information, refer to our [safety data sheet](#).

9. PRODUCT PREPARATION

Affected area	Product mixture
Light cosmetic stains, blemishes, or dull timber	Diluted product (50% of product mixed with 50% clean water)
Stubborn cosmetic stains and blemishes	Undiluted product (neat)

10. PRODUCT APPLICATION

For exterior cladding, apply to the cladding surface from bottom to top to avoid this product running on dry timber.

Apply from a bucket to affected areas, wiping linearly along the full length of the board. Always keep the surface wet and active until the stains or blemishes have faded. The process may take several hours. Continually wipe during the waiting process. Repeat applications may be necessary to remove stubborn stains.

Do not sand or scrape timber to remove stains and blemishes, as this will result in patchy sanding or scraping marks on the timber surface that will show through.

Once the targeted stain or blemish is gone or the timber has brightened, apply the diluted product to even out the area.

Rinse the timber with copious amounts of clean water until all soapiness has gone, particularly in grooves and joints. Use an old towel to dry timber of excess water.

After applying, protect the timber from rain, dust, grime, cement dust, metal filings and other site contaminants before coating.

Once the timber is dry, remove any loose raised fibres (denib) using a 3M griddle scrubber or synthetic scouring pad. Do not use a metal scouring pad.

To recoat, refer the relevant product data sheet for *Dryden WoodOil*, *Dryden OilStain* or *Dryden WoodMaster*.

11. CLEAN UP

Clean up clothing and application tools using detergent and hot water.

12. RESPONSIBLE DISPOSAL

Any remaining product should be disposed of in accordance with local, regional, national, and international regulations.

Leave empty containers open and in a well-ventilated to dry and dispose of via local recycling program.

13. SPILLAGES

This product is slippery when spilt. If this product spills, immediately clear area of unprotected personnel. To clean up the spillage, wear personal protective equipment, absorb the spillage with sand or soil and collect and seal in containers and dispose of responsibly.

14. FIRST AID

- If poisoning occurs, contact the Poisons Information Centre (New Zealand 0800 764 766; Australia 131 126) and have the product container or label at hand.
- If swallowed, give a glass of water, and seek medical assistance. Do not induce vomiting.
- If eye contact occurs, hold eyes open and flood with water for at least 15 minutes. If irritation occurs, seek medical advice.
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs, seek medical advice.
- If inhaled, remove from contaminated area. If not breathing, apply artificial respiration and seek immediate medical advice.
- For special medical advice and emergencies call NZ 0800 734 607 or AU 1800 033 111. For further information, refer to our [safety data sheet](#).

15. FURTHER INFORMATION

For further information:



Contact **0800 379 336** or



Click on www.dryden.co.nz

The sale of this product is subject to our [standard conditions of sale](#).

Dryden is a registered trademark of DuluxGroup (New Zealand) Pty Ltd.